DELABIE

TEMPOMATIC 4 urinal valve



Ref. 430P006

Electronic with integrated batteries

DESCRIPTION

TEMPOMATIC 4 urinal valve - Ref.430P006

Recessed electronic urinal valve:
123 6V Lithium battery-operated.
Satin finish stainless steel wall plate 145 x 145mm with integrated electronics.
Recessing housing:
- Hydraulic connection to the outside.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 105mm).
- Integrated solenoid valve is accessible from the front.
- TEMPOMATIC 4 urinal valve F½" is compatible with sea water and grey water.
Detection delay is 10 seconds.
3 programmes (rinsing volume can be set according to urinal type).
High-frequency mode (exclusive to DELABIE):
- Short rinse after each user.
- Additional rinse at the end of the busy period.
Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use: prevents vacuums.
Flow rate pre-set at 0.3 L/sec. at 3 bar.
Suitable for people with reduced mobility.
10-year warranty.

ADVANTAGES

- Total hygiene: no manual contact
- 3 rinsing programmes and high-frequency mode
- Duty flush prevents proliferation of bacteria

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 urinal valve - Ref.430P006

Technology	Electronic
Height	150 mm
Flow rate	0.3 l/sec
Finish	Satin finish stainless steel
Supply	6V battery
Width	175 mm
Depth	105 - 205 mm





© Delabie