

## TEMPOFLUX urinal valve

Ref. 778BOX-778707

Time flow 7 seconds



### DESCRIPTION

#### TEMPOFLUX urinal valve - Ref.778BOX-778707

Recessed time flow urinal valve:

Satin finish stainless steel wall plate 145 x 145mm.

Chrome-plated metal button.

Waterproof recessing housing:

- Collar with waterproof seal.
- Hydraulic connection from the outside and maintenance from the front.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes from 10 - 120mm (while maintaining the minimum recessing depth of 83mm).
- Suitable for standard or "pipe-in-pipe" supply.
- Stopcock and flow rate adjustment, filter and cartridge are all integrated and accessible from the front.
- TEMPOFLUX F $\frac{1}{2}$ " urinal valve is compatible with sea water and grey water.
- Supplied in 2 kits: secure system flush without sensitive elements.

Soft-touch operation.

Time flow pre-set at ~7 seconds.

Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted up to 0.3 L/sec.

Complies with European standard EN 12541 (class II acoustic level).

Connection with  $\varnothing$  35mm connection washer (for standard urinals) or  $\frac{1}{2}$ " brass connection (for urinals supplied by flexible).

For use with neck tube ref. 752430 or 757430.

Suitable for people with reduced mobility.

10-year warranty.

Kit contents:

(778BOX): recessed housing with cover, collar for waterproofing, valve, time flow cartridge, filter and stopcock.

(778707): control plate, collar for waterproofing, valve, time flow cartridge, filter and stopcock.

### ADVANTAGES



Time flow 7 seconds



Soft-touch operation



Adjustable, modular waterproof housing

## TECHNICAL CHARACTERISTICS

### TEMPOFLUX urinal valve - Ref.778BOX-778707

Technology	Time flow
Height	145 mm
Flow rate	0.15 l/sec
Connector	1/2"
Width	145 mm
Depth	83 - 190 mm

