

## TEMPOFLUX urinal valve

Ref. 778757

Time flow 3 seconds. For DELABIE DELTA urinal







### DESCRIPTION

#### TEMPOFLUX urinal valve - Ref.778757

Exposed time flow urinal valve:  
 For DELABIE DELTA urinal  
 Soft-touch operation.  
 Time flow pre-set at ~3 seconds.  
 Flow rate pre-set at 0.15 L/sec at 3 bar, can be adjusted up to 0.3 L/sec.  
 Innovative stopcock and flow rate adjustment system integrated in the wall plate (patent).  
 Complies with the European standard EN 12541 (class II accoustic level).  
 Chrome-plated solid brass body M $\frac{1}{2}$ ".  
 With chrome-plated neck tube.  
 Angled for recessed inlet.  
 Suitable for people with reduced mobility.  
 Suitable for people with reduced mobility.  
 10-year warranty.

### ADVANTAGES

-  ECO time flow 3 seconds
-  Soft-touch operation
-  Integrated stopcock inside wall plate
-  Sleek and slim design

### TECHNICAL CHARACTERISTICS

#### TEMPOFLUX urinal valve - Ref.778757

Technology	Time flow
Height	330 mm
Flow rate	0.15 l/sec
Connector	1/2"

