

## TEMPOFLUX time flow urinal valve

Ref. 778756

Time flow 3 seconds. For DELABIE DELTACÉRAM urinals.

### DESCRIPTION

#### TEMPOFLUX time flow urinal valve - Ref.778756

Exposed time flow urinal valve:  
For DELABIE DELTACÉRAM urinals.  
Wall-mounted exposed installation.  
Soft-touch operation.  
Time flow pre-set at ~3 seconds.  
Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted up to 0.3 L/sec.  
Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).  
Complies with European standard EN 12541 (class II acoustic level).  
Chrome-plated solid brass body M $\frac{1}{2}$ ".  
With chrome-plated neck tube.  
Angled for recessed inlet.  
Suitable for people with reduced mobility.  
10-year warranty.




### TECHNICAL CHARACTERISTICS

#### TEMPOFLUX time flow urinal valve - Ref.778756

Technology	Time flow
Height	313 mm
Flow rate	0.15 l/sec
Connector	1/2"



### ADVANTAGES

-  ECO time flow 3 seconds
-  Soft-touch operation
-  Stopcock built-in to wall plate
-  Sleek design

