DELABIE

TEMPOFLUX time flow urinal valve



Ref. 778755

Time flow 3 seconds. For standard urinals Ø 35mm.
Straight neck tube

DESCRIPTION

TEMPOFLUX time flow urinal valve - Ref.778755

Exposed time flow urinal valve:
For standard or siphon action urinals.
For wall-mounted exposed installation.
Soft-touch operation.
Time flow pre-set at 3 seconds.
Vacuum breaker.
Flow rate pre-set at 0.15 l/sec. at 3 bar, can be adjusted up to 0.3 l/sec.
Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).
Complies with European standard EN 12541 (acoustic level class II).
Chrome-plated solid brass body M½".
With a chrome-plated neck tube and connection washer Ø 35mm.
Angled for recessed inlet .
Suitable people with reduced mobility.
10-year warranty.


ADVANTAGES

- ECO time flow 3 seconds
- Soft-touch operation
- Stopcock built-in to wall plate
- Smooth design

TECHNICAL CHARACTERISTICS

TEMPOFLUX time flow urinal valve - Ref.778755

Technology	Time flow
Height	320 mm
Flow rate	0.15 l/sec.
Connector	1/2"



© Delabie