

TEMPOFLUX time flow urinal valve

Ref. 778765

Time flow 7 seconds. For standard urinal Ø 35mm. In-line tube







DESCRIPTION

TEMPOFLUX time flow urinal valve - Ref.778765

Exposed time flow urinal valve:
 For standard or siphon action urinals.
 Wall-mounted exposed installation.
 Soft-touch operation.
 Time flow pre-set at ~7 seconds.
 Vacuum breaker.
 Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted up to 0.3 L/sec.
 Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).
 Complies with European standard EN 12541 (class II acoustic level).
 Chrome-plated solid brass body M $\frac{1}{2}$ ".
 30mm in-line chrome-plated tube and connection washer Ø 35mm.
 Angled for recessed inlet.
 Suitable for people with reduced mobility.
 10-year warranty.

ADVANTAGES

-  Time flow 7 seconds
-  Soft-touch operation
-  Stopcock built-in to wall plate
-  Sleek design

TECHNICAL CHARACTERISTICS

TEMPOFLUX time flow urinal valve - Ref.778765

Technology	Time flow
Height	320 mm
Flow rate	0.15 l/sec
Connector	1/2"
Width to the wall	50 mm

