# TEMPOMATIC 4 electronic tap

Ref. 440006

Integrated batteries, stopcock



## **DESCRIPTION**

### TEMPOMATIC 4 electronic tap - Ref.440006

Deck-mounted electronic basin tap:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated metal body.

Cap fixed in place by 2 concealed screws.

PEX flexible with stopcock F3/8" and filter.

Fixing reinforced by two stainless steel rods.

Anti-blocking security.

Suitable for people with reduced mobility.

10-year warranty.

### **ADVANTAGES**



Total hygiene: no manual contact



90% water savings



Batteries integrated into the body of the tap



Anti-bacterial proliferation duty flush

# TECHNICAL CHARACTERISTICS

# **TEMPOMATIC 4 electronic tap - Ref.440006**

Technology	Electronic
Flow rate	3 lpm
Connector	F3/8"
Supply	6V batteries
Drop Height	75 mm
Spout Length	110 mm
Installation:	Deck-mounted

