

KOMPACT TC washbasin and floor-standing WC combination

Ref. 166700

Polished satin 304 stainless steel - Cross wall - Floor standing WC left side

DESCRIPTION

KOMPACT TC washbasin and floor-standing WC combination -

Ref.166700

Combination unit: washbasin and floor-standing WC pan on left sidewith recessed toilet roll holder.

Service duct installation (through-the-wall).

Bacteriostatic 304 stainless steel.

Polished satin finish.

Stainless steel unit thickness: 2mm.

Rounded corners and edges for improved safety.

Smooth surface for easy cleaning.

Suitable for prisons, police stations, etc.

WC pan is completely welded to washbasin, no screws:

makes cleaning easier and prevents concealment of objects.

Washbasin equipped with time flow tap: stainless steel tamperproofpush-button and anti-blocking system, 7 second time flow, M1/2".

WC equipped with time flow flush valve, 7 second time flow, M3/4".

Water inlet: washbasin M1/2", WC M3/4".

Recessed horizontal water outlet: Ø 100mm.

200mm threaded rod can be cut to size (other lengths available on demand).

Weight: 30kg.

[Formerly ref: 0616130007]

TECHNICAL CHARACTERISTICS

KOMPACT TC washbasin and floor-standing WC combination -

Ref.166700

Height	1000 mm
Length	615 mm
Finish	Polished satin 304 stainless steel
Width	725 mm
Thickness	2 mm



ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

