DELABIE

KOMPACT washbasin and wall-hung WC combination



Ref. 160500

Polished satin 304 stainless steel - Wall mounted - Floor mount central WC

DESCRIPTION

KOMPACT washbasin and wall-hung WC combination - Ref.160500

Combination unit: washbasin and WC pan suspended centrallywith recessed toilet roll holder.
Wall-mounted installation with 3 access panels, 2 on the sidesand 1 on the top with theft prevention TORX security screws.
Bacteriostatic 304 stainless steel.
Polished satin finish.
Stainless steel unit thickness: 2mm.
Rounded corners and edges for improved safety.
Smooth surface for easy cleaning.
Suitable for prisons, police stations, etc.
WC pan is completely welded to washbasin, no screws:
makes cleaning easier and prevents concealment of objects.
Washbasin equipped with time flow tap: stainless steel tamperproofpush-button and anti-blocking system, 7 second time flow, M1/2".
WC equipped with time flow flush valve, 7 second time flow, M3/4".
Water inlet: washbasin M1/2", WC M3/4".
Recessed horizontal water outlet: Ø 100mm
Supplied with washbasin siphon.
Easy installation: only one water outlet for both washbasin and WC,water inlet and outlet already connected.
Weight: 36kg
[Formerly ref: 0610030005]


ADVANTAGES

- Bacteriostatic 304 stainless steel
- Suitable for secure sector

TECHNICAL CHARACTERISTICS

KOMPACT washbasin and wall-hung WC combination - Ref.160500

Height	1000 mm
Length	735 mm
Finish	Polished satin 304 stainless steel
Width	725 mm
Thickness	2 mm



© Delabie