90¼ wall grab bar stainless steel brushed left



Ref. GW11 15 04 01

AISI 304 stainless steel, satin

DESCRIPTION

90¼ wall grab bar stainless steel brushed left - Ref.GW11 15 04 01

Technical specifications:
90 ¼ angled bar with 3 with three points of support.
The tube has an outside diameter of 32 mm with a thickness of 1,5 mm.
The three mounting flanges are made of zinc-plated stainless steel plate with
anticorrosion treatment of 2.5 mm of thickness and 75 mm of diameter.
The endings of the tube and the mounting flanges are threading M10.
Mounting flanges have three holes for wall attachment and snap
flange covers with 0.5 mm of thickness.
Clearance between the grab bar and wall is 43mm.
The assembled unit has suitable resistance to corrosion.
The grab bar is fixed to the wall by means of 9 nylon wall plugs
8X50 and AISI 304 stainless steel screws 5X60.
Grab bar will support loads in excess of 120Kg if properly installed

ADVANTAGES

- Anti-fingerprint treatment
- Easily removable head

TECHNICAL CHARACTERISTICS

90¼ wall grab bar stainless steel brushed left - Ref.GW11 15 04 01

Height	800mm
Length	400mm
Finish	AISI 304 stainless steel, satin
Width	76mm
Thickness	1.5mm
Diameter	32mm

© Genwec