3 sides grab bar stainless steel brushed left



Ref. GW11 20 04 01

AISI 304 stainless steel, satin

DESCRIPTION

3 sides grab bar stainless steel brushed left - Ref.GW11 20 04 01

3-sided angled bar with 4 points of support.
The tube has an outside diameter of 32 mm with a thickness of 1,5 mm.
The mounting flanges are made of zinc-plated stainless steel plate with anticorrosion treatment
of 2.5 mm of thickness and 75 mm of diameter.
The endings of the tube and the mounting flanges are threading M10.
Mounting flanges have three holes for wall attachment and snap flange covers with 0.5 mm of thickness.
The assembled unit has suitable resistance to corrosion.
The grab bar is fixed to the wall by means of nylon wall plugs 8X50 and AISI 304 stainless steel screws 5X60.
Grab bar will support loads in excess
of 120Kg if properly installed.
The total measures of the product are 760 x 460 x 610 mm.

ADVANTAGES

- Anti-fingerprint treatment
- Easily removable head

TECHNICAL CHARACTERISTICS

3 sides grab bar stainless steel brushed left - Ref.GW11 20 04 01

Height	760mm
Finish	AISI 304 stainless steel, satin
Width	460mm 610mm
Thickness	1.5mm
Diameter	32mm

© Genwec