Phenolic folding seat brushed

Ref. GW11 23 11 00

AISI 304 stainless steel, satin



DESCRIPTION

Phenolic folding seat brushed - **Ref.GW11 23 11 00**

The folding shower seat is manufactured in an AISI 304 stainless steel structure attached to a one-piece phenol formaldehyde resin seat.
Its structure manufactured in AISI 304 stainless steel, 32 mm diameter, 1.5 mm thickness, is fixed to two wall supports manufactured in AISI 304 stainless steel, 3mm thickness.
The structure turns 90¼ to the wall supports in order to be able to leave the seat in upright position.
The seating surface screwed to the structure is made of high resistance phenol formaldehyde resin.
The assembled unit has a satin finish and its materials assure a correct maintenance and cleaning.
The shower seat is fixed to the wall with 8 screws 8 x70mm and 8 nylon wall plugs 10x50 mm to support static loads of 120Kg.
The total measures of the product are 190x493,2x451,4 mm.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Phenolic folding seat brushed - **Ref.GW11 23 11 00**

Height	190
Length	450
Finish	AISI 304 stainless steel, satin
Depth	367
Thickness	1.5mm
Diameter	32mm

© Genwec