

TEMPOMATIC 4 electronic tap

Ref. 44000115

Plug-in mains supply, 15mm stopcock



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref.44000115





Deck-mounted electronic basin tap:
230/6V plug-in mains supply.
Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after the last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated solid brass body.
Cap fixed in place by two concealed screws.
PEX flexible with stopcock, filter and Ø 15mm conical inlet.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
10-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref.44000115

| | |
|---------------|-------------------------------|
| Technology | Electronic |
| Flow rate | 3 lpm |
| Connector | M1/2" Ø 15mm |
| Supply | 230/6V (plug-in mains supply) |
| Supply | 230/6V mains supply (plug-in) |
| Drop Height | 75 mm |
| Spout Length | 110 mm |
| Installation: | Deck-mounted |

ADVANTAGES

-  Total hygiene: no manual contact
-  90% water savings
-  Plug-in mains supply
-  Anti-bacterial proliferation duty flush

