

## Angled Nylon grab bar 135<sub>i</sub>, white, anti-bacterial, 220 x 220mm

Ref. 5083N

Bright white HR anti-bacterial Nylon, NylonClean, 3 fixing points







### DESCRIPTION

**Angled Nylon grab bar 135<sub>i</sub>, white, anti-bacterial, 220 x 220mm -**

**Ref.5083N**

Angled grab bar 135<sub>i</sub>, ̄ 32mm, for people with reduced mobility.  
Angled grab bar made from bright white HR Nylon.  
For use as a handrail (horizontal part) or as a grab bar (135<sub>i</sub> part ) for WCs, showers or baths.  
NylonClean anti-bacterial treatment: optimal protection against bacterial and mould development.  
Universal for either left or right side.  
Suitable for intensive use in public places or the healthcare sector.  
High strength polyamide (Nylon): with 2mm reinforced steel core treated against corrosion.  
Uniform non-porous surface for easy maintenance and hygiene.  
Good resistance to chemical products and cleaning.  
Anti-UV treatment: prevents yellowing.  
Warm to the touch.  
38mm gap between the bar and the wall: minimal space prevents the forearm passing between the bar and the wall, reducing the risk of fracture in case of loss of balance.  
3 fixing points prevent the hand from getting trapped and simplify installation.  
Concealed fixings secured by a 6-hole plate, ̄ 72mm.  
Supplied with stainless steel screws for concrete walls.  
Dimensions: 220 x 220mm.  
Tested to over 200kg. Maximum recommended user weight 135kg.  
10-year warranty.  
CE marked.

### ADVANTAGES

-  NylonClean anti-bacterial treatment
-  Tested to over 200kg
-  38mm gap from the wall: space saving
-  HR Nylon: smooth surface is easy to clean

## TECHNICAL CHARACTERISTICS

Angled Nylon grab bar 135j, white, anti-bacterial, 220 x 220mm -

### Ref.5083N

Height	220mm
Length	220mm
Finish	HR anti-bacterial Nylon, bright white
Thickness	Nylon
Thickness	Nylon
Width to the wall	38mm
Diameter	32mm
Destination	For WCs

