DELABIE

Angled grab bar 90¡, ¯ 32mm

Ref. 5180S

UltraSatin polished satin stainless steel



DESCRIPTION

Angled grab bar 90¡, ¯ 32mm- Ref.5180S

Angled grab bar 90¡ for people with reduced mobility.
For use as a handrail (horizontal part) or as a grab bar (vertical part) for WCs or baths.
Universal for either left or right side.
Dimensions: 300 x 300mm, ¯ 32mm.
Bacteriostatic 304 stainless steel tube.
UltraSatin polished satin stainless steel, uniform non-porous surface for easy maintenance and hygiene.
Plate welded to the tube by invisible safety bead weld (process exclusive to "ArN-Securit").
40mm gap between the bar and the wall: minimal space prevents the forearm passing between the bar and the wall, reducing the risk of fracture in case of loss of balance.
Concealed fixings, secured to wall by a 3-hole, 304 stainless steel plate, ¯ 72mm.
Fixing plates and cover plates in 304 stainless steel.
Supplied with stainless steel screws for concrete walls.
Tested to over 200kg. Maximum recommended user weight: 135kg.
10 year warranty. CE marked.


ADVANTAGES

- 304 stainless steel: reduces bacterial development
- Tested to over 200kg
- 40mm gap between bar and wall: minimal space
- UltraSatinbasin: Smooth surface easy to clean

TECHNICAL CHARACTERISTICS

Angled grab bar 90¡, ¯ 32mm- Ref.5180S

Height	300mm
Length	300mm
Finish	304 stainless steel UltraSatin polished satin
Width to the wall	40mm
Diameter	Ø 32mm
Destination	For WCs For baths



© Delabie