

## TEMPOMATIC 3 electronic tap

Ref. 443006

Integrated battery



### DESCRIPTION

#### TEMPOMATIC 3 electronic tap - Ref.443006

Wall-mounted electronic basin tap:  
 Battery-operated with integrated 223 6V Lithium batteries.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated solid brass body.  
 Cap fixed in place by 2 concealed screws, with pictogram to identify the sensor easily.  
 Wall-mounted, M1/2".  
 Ø 50mm, L. 190mm.  
 Anti-blocking security.  
 Suitable for people with reduced mobility.  
 10-year warranty.

### TECHNICAL CHARACTERISTICS

#### TEMPOMATIC 3 electronic tap - Ref.443006

Technology	Electronic
Flow rate	3 lpm
Connector	M1/2"
Supply	6V battery
Supply	6V batteries
Spout Length	190 mm
Installation:	Wall-mounted

### ADVANTAGES



Total hygiene: no manual contact



90% water savings



Battery integrated into the body of the tap



Anti-bacterial proliferation duty flush

