BINOPTIC electronic tap

Ref. 379DER

Mains supply



DESCRIPTION

BINOPTIC electronic tap - Ref.379DER

Electronic basin tap for cross wall installation.

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm. Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Filters and solenoid valves M3/8".

Chrome-plated brass body.

Chrome-plated spout L. 205mm for cross wall installation? 190mm.

Cable for sensor L. 120mm, flexibles and mounting all pass through the same hole.

Anti-blocking security.

Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).

Suitable for people with reduced mobility.

10-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref.379DER

Technology	Electronic
Flow rate	3 lpm
Connector	M3/8"
Supply	230/12V mains supply
Spout Length	205 mm
Installation:	Cross wall

