

TEMPOMATIC 4 electronic tap

Ref. 443506

Integrated batteries



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref.443506

Wall-mounted electronic basin tap:
 Battery-operated with integrated 123 6V Lithium batteries.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated metal body L. 190mm
 Cap fixed in place by 2 concealed screws.
 Stopcock.
 Wall-mounted.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 10-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Batteries integrated into the body of the tap



Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref.443506

Technology	Electronic
Flow rate	3 lpm
Connector	M1/2"
Supply	6V batteries
Spout Length	190 mm
Installation:	Wall-mounted

