# SECURITHERM EP pressure-balancing basin mixer

Ref. 2446EP

Wall-mounted mixer with swivelling spout L. 150mm, sculptured lever



# DESCRIPTION

### SECURITHERM EP pressure-balancing basin mixer - Ref.2446EP

Wall-mounted SECURITHERM Pressure Balancing (EP) basin mixer. Anti-scalding safety: HW flow is reduced if CW supply fails (and vice versa). Securitouch thermal insulation prevents burns.

Flat, swivelling under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.

 $\ensuremath{\mathcal{Q}}$  40mm pressure-balancing ceramic cartridge and pre-set maximum temperature limiter.

Body and spout with smooth interiors and low water volume (reduces niches where bacteria can develop).

Flow rate regulated at 5 lpm.

Body and spout with smooth interior and low water volume (reduces bacterial development).

Chrome-plated brass body.

Sculptured control lever.

Supplied with STOP/CHECK connectors M1/2" M3/4" ideal for use in hospitals.

10-year warranty.

# ADVANTAGES

# TECHNICAL CHARACTERISTICS

# SECURITHERM EP pressure-balancing basin mixer - Ref.2446EP

Technology	SECURITHERM EP, Securitouch
Flow rate	5 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Spout Length	150 mm
Temperature limiter	41 °C

