

SECURITHERM thermostatic basin mixer

Ref. H9600

Sequential thermostatic mixer H.95mm L.120mm,
Hygiene lever L. 146mm



DESCRIPTION

SECURITHERM thermostatic basin mixer - Ref.H9600

Deck-mounted SECURITHERM thermostatic basin mixer.
Thermostatic sequential mixer: opens and closes with cold water.
Single hole mixer with curved spout H. 95mm L. 120mm fitted with a hygienic flow straightener.
No risk of cross flow between hot and cold water.
Mixer has no non-return valves on the inlets.
Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant sequential thermostatic cartridge for single lever control of flow rate and temperature.
Temperature can be adjusted from cold water up to 40°C with temperature limiter set at 40°C.
Thermal or chemical shocks are possible.
Body and spout with smooth interiors and low water volume.
Flow rate limited to 5 lpm at 3 bar.
No manual contact thanks to Hygiene control lever L. 146mm.
No pop-up waste.
PEX flexibles F3/8" with stopcocks.
Fixing reinforced by 2 stainless steel rods.
SECURITHERM thermostatic mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 10-year warranty.
Also available with copper tails.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic basin mixer - [Ref.H9600](#)

Technology	SECURITHERM Securitouch sequential mixer
Flow rate	5 lpm at 3 bar
Connector	F3/8"
Finish	Chrome-plated brass
Drop Height	95 mm
Spout Length	120 mm
Temperature limiter	Yes

