Electronic sink mixer with BIOCLIP removable spout

Ref. 20871T3

Single hole infrared tall mixer, disposable, swivelling spout



ADVANTAGES

DESCRIPTION

Electronic sink mixer with BIOCLIP removable spout - Ref.20871T3

Deck-mounted electronic sink mixer.

Electronic mixer with high, swivelling, removable BIOCLIP spout H. 300mm. Single hole mixer supplied with 1 disposable, recyclable Hostaform® spout L. $180 \text{mm} \ \emptyset \ 22 \text{mm}$.

Independent IP65 electronic control unit.

Mains supply with 230/12V transformer.

Body and spout with smooth interiors (reduce niches where bacteria can develop).

Adjustable duty flush (pre-set flush for approximately 60 seconds every 24 hours after the last use) to prevent stagnation in the water supply if the system is not used for prolonged periods.

Flow rate limited to 9 lpm at 3 bar.

Shock-resistant infrared presence detection sensor.

Chrome-plated solid brass body and base and reinforced fixing via 2 stainless steel rods.

Hygiene lever L. 100mm controls temperature.

PEX flexibles with filters and M3/8" solenoid valves.

Anti-blocking security.

Solenoid valves upstream of the mixing chamber.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.

Two shut-off options:

- standard mode timed flow with automatic shut-off;
- ON/OFF mode user shuts off flow voluntarily or automatic shut-off after 30 minutes.

Thermal shocks are possible.

Position the sensor on the side of the mixer in On/Off mode.

DELABIE

TECHNICAL CHARACTERISTICS

Electronic sink mixer with BIOCLIP removable spout - Ref.20871T3

Technology	Electronic mixe
Height	420 mm
Flow rate	9 lpm
Connector	M3/8"
Finish	Chrome-plated brass
Drop Height	300 mm
Spout Length	180 mm

