

## SECURITHERM thermostatic sink mixer

Ref. H9612

Single hole thermostatic mixer with retracting hand spray



### DESCRIPTION

#### **SECURITHERM thermostatic sink mixer - Ref.H9612**

Deck-mounted SECURITHERM thermostatic basin mixer.  
Sequential thermostatic mixer: opens and closes with cold water.  
Perfectly suited to baby baths.  
Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails.  
Securitouch thermal insulation prevents burns.  
No risk of cross flow between the hot and cold water.  
No non-return valves on the inlets.  
Single hole mixer with swivelling spout H. 105mm L. 200mm.  
Retracting hand spray with 2 jet options: flow straightener/rain effect.  
Scale-resistant sequential thermostatic cartridge for sequential control of the flow rate and temperature.  
Temperature control: cold water to 40°C.  
Maximum temperature limiter set at 40°C.  
Body with smooth interior.  
Flow rate regulated at 3 lpm.  
No manual contact thanks to Hygiene control lever L. 100mm.  
Mixed water brass outlet L. 105mm.  
BIOSAFE flexible shower hose reduces bacterial proliferation: transparent polyurethane, smooth interior and exterior.  
Flexible with narrow interior Ø 6mm: low water volume.  
Specific counterweight.  
PEX flexibles F3/8".  
Fixing reinforced by 2 stainless steel rods.  
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
Suitable for people with reduced mobility.  
10-year warranty.

### ADVANTAGES

## TECHNICAL CHARACTERISTICS

### SECURITHERM thermostatic sink mixer - Ref.H9612

Technology	SECURITHERM sequential Securitouch
Flow rate	3 lpm
Connector	F3/8"
Finish	Chrome-plated brass
Drop Height	105 mm
Spout Length	200 mm
Temperature limiter	40 °C

