

TEMPOMATIC MIX PRO electronic mixer

Ref. 49525315

Mains supply, Ø 15mm conical inlets

DESCRIPTION

TEMPOMATIC MIX PRO electronic mixer - Ref.49525315

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shock-resistant infrared presence detection sensor.
Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods.
PEX flexibles with filters and solenoid valves Ø 15mm for compression fitting.
360° swivelling spout with smooth interior (reduces bacterial development).
Removable spout for cleaning.
Anti-blocking security.
Side temperature control with adjustable maximum temperature limiter and long ergonomic lever.
10-year warranty.

Two shut-off options:

Standard mode: timed flow with automatic shut-off

ON/OFF mode: user shuts off voluntarily or automatic shut-off after 30 minutes of flow. Thermal shocks are possible.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX PRO electronic mixer - Ref.49525315

Technology	Electronic
Flow rate	4 lpm
Connector	M1/2" Ø 15mm
Supply	230/12V mains supply
Drop Height	310 mm
Spout Length	200 mm
Installation:	Deck-mounted



ADVANTAGES



Total hygiene: no manual contact



85% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

