

TEMPOMATIC MIX 2 electronic mixer

Ref. 494000

Electronic mains supply

DESCRIPTION

TEMPOMATIC MIX 2 electronic mixer - Ref.494000

Deck-mounted electronic basin mixer:
 Independent IP65 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Shock-resistant infrared presence detection sensor.
 Chrome-plated solid brass body.
 PEX flexibles with filters and solenoid valves M3/8".
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Side temperature control with adjustable maximum temperature limiter.
 Solenoid valves are upstream of the mixing chamber.
 Suitable for people with reduced mobility.
 10-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 2 electronic mixer - Ref.494000

Technology	Electronic
Flow rate	4 lpm
Connector	M3/8"
Supply	230/12V mains supply
Drop Height	125 mm
Spout Length	145 mm
Installation:	Deck-mounted



ADVANTAGES



Total hygiene: no manual contact



85% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

