

## BINOPTIC electronic tap

Ref. 398015

Mains







### DESCRIPTION

#### BINOPTIC electronic tap - Ref.398015

Deck-mounted electronic basin tap:  
 Independent IP65 electronic control unit.  
 230/12V mains supply with transformer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated brass body.  
 PEX flexible with filter and solenoid valve M?".  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Spout with smooth interior and low water volume (reduces bacterial development).  
 Drop height: 250mm for countertop washbasins.  
 Suitable for people with reduced mobility.  
 10-year warranty.

### ADVANTAGES

-  90% water savings
-  Total hygiene: no manual contact
-  Sleek design
-  Anti-bacterial proliferation duty flush

### TECHNICAL CHARACTERISTICS

#### BINOPTIC electronic tap - Ref.398015

Technology	Electronic
Flow rate	3 lpm
Connector	M3/8"
Supply	230/12V mains supply
Drop Height	250 mm
Spout Length	185 mm
Installation:	Deck-mounted

