

SECURITHERM thermostatic sink mixer

Ref. H9716

Dual control mixer H. 225mm L. 190mm



DESCRIPTION

SECURITHERM thermostatic sink mixer - Ref.H9716

Deck-mounted SECURITHERM thermostatic dual control sink mixer.
Tall, single hole mixer with swivelling tubular spout H. 225mm L.190mm.
Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails.
Spout with smooth interior with hygienic flow straightener, suitable for fitting a BIOFIL terminal filter.
Scale-resistant thermostatic cartridge for adjusting the temperature.
¼-turn ceramic head for adjusting the flow rate.
Temperature can be adjusted, with two temperature limiters: first temperature limiter set at 38°C (can be overridden), and second temperature limiter set at 41°C.
Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water.
Flow rate limited to 9 lpm at 3 bar.
ERGO control knobs.
PEX flexibles F3/8" with filters and non-return valves.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Suitable for people with reduced mobility.
Fixing reinforced by 2 stainless steel rods.
10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic sink mixer - Ref.H9716

Technology	SECURITHERM thermostatic
Flow rate	9 lpm
Connector	F3/8"
Finish	Chrome-plated brass
Drop Height	225 mm
Spout Length	190 mm
Temperature limiter	41 °C

