# SECURITHERM thermostatic sink mixer

Ref. H9716

Dual control mixer H. 225mm L. 190mm



### DESCRIPTION

#### SECURITHERM thermostatic sink mixer - Ref. H9716

Deck-mounted SECURITHERM thermostatic dual control sink mixer. Tall, single hole mixer with swivelling tubular spout H. 225mm L.190mm. Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails. Spout with smooth interior with hygienic flow straightener, suitable for fitting a BIOFIL terminal filter.

Scale-resistant thermostatic cartridge for adjusting the temperature.

1/4-turn ceramic head for adjusting the flow rate.

Temperature can be adjusted, with two temperature limiters: first temperature limiter set at 38°C (can be overidden), and second temperature limiter set at 41°C.

Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water.

Flow rate limited to 9 lpm at 3 bar.

ERGO control knobs.

PEX flexibles F3/8" with filters and non-return valves.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

Fixing reinforced by 2 stainless steel rods.

10-year warranty.

# TECHNICAL CHARACTERISTICS

## SECURITHERM thermostatic sink mixer - Ref.H9716

Flow rate         9 lpm           Connector         F3/8"           Finish         Chrome-plated brass           Drop Height         225 mm           Spout Length         190 mm           Temperature limiter         41 °C	Technology	SECURITHERM thermostatic
Finish Chrome-plated brass Drop Height 225 mm Spout Length 190 mm	Flow rate	9 lpm
Drop Height 225 mm  Spout Length 190 mm	Connector	F3/8"
Spout Length 190 mm	Finish	Chrome-plated brass
, ,	Drop Height	225 mm
Temperature limiter 41 °C	Spout Length	190 mm
	Temperature limiter	41 °C

