

## SECURITHERM thermostatic sink mixer set

Ref. H9613

Sequential mixer and column set

### DESCRIPTION

#### **SECURITHERM thermostatic sink mixer set - Ref.H9613**

SECURITHERM thermostatic sequential sink mixer set and column with retracting hand spray.

Ideal for baby baths.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

Sequential: opens and closes with cold water.

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

Swivelling column H. 200mm L. 220mm.

Retracting hand spray with 2 jet options: flow straightener/rain effect.

Scale-resistant thermostatic sequential cartridge for single control temperature and flow-rate adjustment.

Temperature can be adjusted from cold water to 40°C with maximum temperature limiter set at 40°C.

Body and column with smooth interiors.

Flow rate regulated at 7 lpm.

No manual contact thanks to Hygiene control lever L. 100mm.

Mixed water brass outlet L. 160mm.

BIOSAFE flexible shower hose reduces bacterial proliferation: transparent polyurethane, smooth interior and exterior.

Hose with narrow diameter (internal Ø 6mm): low water volume.

Specific counterweight.

PEX flexibles F3/8" and reinforced fixing via 2 stainless steel rods.

Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.



### ADVANTAGES

## TECHNICAL CHARACTERISTICS

### SECURITHERM thermostatic sink mixer set - Ref.H9613

Technology	SECURITHERM sequential Securitouch
Flow rate	7 lpm
Connector	F3/8"
Finish	Chrome-plated brass
Drop Height	200 mm
Spout Length	220 mm
Temperature limiter	40 °C

