# SECURITHERM Securitouch thermostatic shower mixer

Ref. H9769

Thermostatic shower mixer with no non-return valves



# **DESCRIPTION**

### SECURITHERM Securitouch thermostatic shower mixer - Ref. H9769

SECURITHERM dual control thermostatic shower mixer.

Thermostatic mixer with no non-return valves on the inlets (reduced bacterial proliferation).

No risk of cross flow between hot and cold water.

Anti-scalding failsafe: shuts off automatically if cold supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails.

Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic cartridge for temperature adjustment.

1/4-turn ceramic head for flow rate adjustment.

Temperature control up to 41°C.

Double temperature limiter: 1st limiter set at 38°C, 2nd limiter set at 41°C.

Thermal shocks are possible without removing the control knob or shutting off the cold water supply.

Flow rate limited to 9 lpm at 3 bar.

Ergonomic controls.

M½" shower outlet.

F¾" inlets with integrated filters.

Mixer supplied with offset STOP/CHECK wall connectors M½" M¾".

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics

10-year warranty.

## **ADVANTAGES**

# **TECHNICAL CHARACTERISTICS**

## SECURITHERM Securitouch thermostatic shower mixer - Ref.H9769

Technology	SECURITHERM dual control thermostatic mixer, Securitouch, no-non-return valves
Length	260 mm
Flow rate	8 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	41 °C
Depth	95 mm

