

SECURITHERM

Securitouch thermostatic shower mixer

Ref. H9769

Thermostatic shower mixer with no non-return valves



DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref.H9769

SECURITHERM dual control thermostatic shower mixer.
Thermostatic mixer with no non-return valves on the inlets (reduced bacterial proliferation).
No risk of cross flow between hot and cold water.
Anti-scalding failsafe: shuts off automatically if cold supply fails.
Prevents cold showers: shuts off automatically if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic cartridge for temperature adjustment.
¼-turn ceramic head for flow rate adjustment.
Temperature control up to 41°C.
Double temperature limiter: 1st limiter set at 38°C, 2nd limiter set at 41°C.
Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
Flow rate limited to 9 lpm at 3 bar.
Ergonomic controls.
M½" shower outlet.
F¾" inlets with integrated filters.
Mixer supplied with offset STOP/CHECK wall connectors M½" M¾".
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics
10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref.H9769

Technology	SECURITHERM dual control thermostatic mixer, Securitouch, no non-return valves
Length	260 mm
Flow rate	8 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	41 °C
Depth	95 mm

