SECURITHERM Securitouch thermostatic shower mixer

Ref. H9741

Dual control thermostatic shower mixer



DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref.H9741

SECURITHERM dual control thermostatic shower mixer.

Thermostatic mixer with anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.

Securitouch thermal insulation to prevent burns.

Scale-resistant thermostatic cartridge for temperature adjustment.

1/4-turn ceramic head for flow rate adjustment.

Temperature control from 25 - 41°C.

Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41°C.

Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water supply.

Flow rate regulated at 9 lpm.

Chrome-plated brass body and ERGO controls.

M1/2" shower outlet.

F3/4" inlets with integrated filters and non-return valves.

Wall-mounted mixer with offset M1/2" M3/4" STOP/CHECK connectors.

Mixer ideal for healthcare facilities, retirement and care home, hospitals and clinics.

10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref.H9741

Technology	SECURITHERM dual control thermostatic, Securitouch
Length	286 mm
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	41 °C
Depth	95 mm

