

## SECURITHERM thermostatic shower mixer

Ref. H9768TP

Thermostatic mixer without non-return valves



### DESCRIPTION

#### SECURITHERM thermostatic shower mixer - Ref.H9768TP

SECURITHERM dual control thermostatic shower mixer.  
Thermostatic mixer with no non-return valves on the inlets (reduced bacterial proliferation).  
No risk of cross flow between hot and cold water.  
Anti-scalding failsafe: shuts off automatically if cold water supply fails.  
Prevents cold showers: shuts off automatically if hot water supply fails.  
Securitouch thermal insulation prevents burns.  
Scale-resistant thermostatic cartridge for temperature adjustment.  
¼-turn ceramic head for flow rate adjustment.  
Temperature control up to 41°C.  
Thermal shocks are possible without shutting off the cold water supply.  
Flow rate limited to 9 lpm at 3 bar.  
ERGO controls.  
M½" shower outlet.  
F¾" inlets with integrated filters.  
Mixer with inline STOP/CHECK wall connectors M1/2" M3/4".  
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
10-year warranty.

### ADVANTAGES

### TECHNICAL CHARACTERISTICS

#### SECURITHERM thermostatic shower mixer - Ref.H9768TP

Technology	SECURITHERM thermostatic dual control, Securitouch, with no non-return valves
Length	260 mm
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	41 °C