

SECURITHERM

Securitouch thermostatic shower mixer

Ref. H9741S

Dual control thermostatic mixer



DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref.H9741S

SECURITHERM dual control thermostatic shower mixer.
 Thermostatic mixer with anti-scalding failsafe: shuts off automatically if cold or hot water supply fails (and vice versa).
 Securitouch thermal insulation to prevent burns.
 Scale-resistant thermostatic cartridge for temperature adjustment.
 1/4-turn ceramic head for flow rate adjustment.
 Temperature control from 25 - 41°C.
 Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41°C.
 Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water.
 Flow rate regulated at 9 lpm.
 Chrome-plated brass body and ERGO controls.
 M1/2" shower outlet.
 F3/4" inlets with integrated filters and non-return valves.
 Wall-mounted mixer with M1/2" M3/4" off-set standard connectors.
 Mixer ideal for healthcare facilities, retirement and care home, hospitals and clinics.
 10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref.H9741S

Technology	SECURITHERM dual control thermostatic, Securitouch
Length	286 mm
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	41 °C
Depth	84 mm

