# SECURITHERM Securitouch thermostatic shower mixer

Ref. H9741S

Dual control thermostatic mixer



### **DESCRIPTION**

### SECURITHERM Securitouch thermostatic shower mixer - Ref.H9741S

SECURITHERM dual control thermostatic shower mixer.

Thermostatic mixer with anti-scalding failsafe: shuts off automatically if cold or hot water supply fails (and vice versa).

Securitouch thermal insulation to prevent burns.

Scale-resistant thermostatic cartridge for temperature adjustment.

1/4-turn ceramic head for flow rate adjustment.

Temperature control from 25 - 41°C.

Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41°C.

Thermal shocks are are easy to undertake without removing the control knob or shutting off the cold water.

Flow rate regulated at 9 lpm.

Chrome-plated brass body and ERGO controls.

M1/2" shower outlet.

F3/4" inlets with integrated filters and non-return valves.

Wall-mounted mixer with M1/2" M3/4" off-set standard connectors.

Mixer ideal for healthcare facilities, retirement and care home, hospitals and clinics.

10-year warranty.

# **ADVANTAGES**

## TECHNICAL CHARACTERISTICS

# SECURITHERM Securitouch thermostatic shower mixer - Ref.H9741S

| Technology          | SECURITHERM dual control thermostatic, Securitouch |
|---------------------|--|
| Length              | 286 mm   |
| Flow rate           | 9 lpm  |
| Connector           | M1/2"  |
| Finish              | Chrome-plated brass                                |
| Temperature limiter | 41 °C  |
| Depth               | 84 mm  |

