

SECURITHERM

Securitouch thermostatic shower mixer

Ref. 9741

Dual control with thermal insulation



DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref.9741

SECURITHERM dual control thermostatic shower mixer:
 Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
 Securitouch thermal insulation prevents burns.
 Scale-resistant thermostatic cartridge to adjust the temperature.
 1/4-turn ceramic head for flow rate adjustment.
 Temperature control from 25 - 41°C.
 Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41°C.
 Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
 Flow rate regulated at 9 lpm.
 Chrome-plated brass body and ERGO control knobs.
 M1/2" shower outlet.
 F3/4" inlets with integrated filters and non-return valves.
 Mixer with no wall connectors.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref.9741

Technology	SECURITHERM dual control thermostatic mixer, Securitouch
Length	286 mm
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Depth	95 mm

