

Sequential thermostatic shower mixer

Ref. H9630

Thermostatic mixer with no non-return valves, bottom outlet



DESCRIPTION

Sequential thermostatic shower mixer - [Ref.H9630](#)

SECURITHERM thermostatic sequential shower.

Thermostatic sequential mixer: opens and closes with cold water.

Mixer with no non-return valves on the inlets (reduces bacterial proliferation).

No risk of cross flow between hot and cold water.

Sequential mixer with anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic sequential cartridge adjusts the flow rate and the temperature.

Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.

Thermal shocks are possible.

Body with smooth interior and low water volume (reduces niches where bacteria can develop).

Flow rate regulated at 9 lpm.

Chrome-plated brass body and Hygiene control lever L. 100mm.

M1/2" bottom shower outlet.

Wall-mounted mixer with offset STOP/CHECK connectors, M1/2" M3/4".

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - [Ref.H9630](#)

Technology	SECURITHERM sequential thermostatic shower, Securitouch
Length	184 mm
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	39 °C

