

## Sequential thermostatic shower mixer

Ref. H964015

SECURITHERM sequential mixer, top outlet



### DESCRIPTION

#### Sequential thermostatic shower mixer - Ref.H964015

SECURITHERM thermostatic sequential shower mixer.  
 Thermostatic sequential mixer: opens and closes with cold water.  
 Mixer with no non-return valves (limits bacterial proliferation).  
 No risk of cross flow between hot and cold water.  
 Sequential mixer with anti-scalding safety: shuts off automatically if hot or cold water supply fails.  
 Securitouch thermal insulation prevents burns.  
 Scale-resistant thermostatic sequential cartridge controls flow rate and temperature.  
 Temperature can be adjusted from cold water to 39°C with maximum temperature limiter set at 39°C.  
 Thermal shocks are possible.  
 Body with smooth interior and low water volume (reduces niches where bacteria can develop).  
 Flow rate regulated at 9 lpm.  
 Chrome-plated brass body and Hygiene control lever L. 100mm.  
 M3/4" top shower outlet.  
 Wall-mounted mixer with inline STOP/CHECK connectors, M1/2" M3/4".  
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Suitable for people with reduced mobility.  
 10-year warranty.

### ADVANTAGES

### TECHNICAL CHARACTERISTICS

#### Sequential thermostatic shower mixer - Ref.H964015

Technology	Sequential thermostatic SECURITHERM securitouch
Flow rate	9 lpm
Finish	Chrome-plated brass
Temperature limiter	39 °C
Width	184 mm

