

Sequential thermostatic shower mixer

Ref. H9630S

Thermostatic mixer with no non-return valves, bottom outlet



DESCRIPTION

Sequential thermostatic shower mixer - Ref.H9630S

SECURITHERM thermostatic sequential shower mixer.
Thermostatic sequential mixer: opens and closes with cold water.
Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
No risk of cross flow between hot and cold water.
Sequential mixer with anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic sequential cartridge adjusts the flow rate and the temperature.
Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.
Thermal shocks are possible.
Body with smooth interior and low water volume (reduces niches where bacteria can develop).
Flow rate regulated at 9 lpm.
Chrome-plated brass body and Hygiene control lever L. 100mm.
M1/2" bottom shower outlet.
Wall-mounted mixer with offset standard connectors M1/2", M3/4".
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Suitable for people with reduced mobility.
10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - Ref.H9630S

Technology	SECURITHERM single control, Securitouch
Length	184 mm
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	39 °C

