

SECURITHERM thermostatic shower mixer

Ref. H9739S

Dual control mixer



DESCRIPTION

SECURITHERM thermostatic shower mixer - Ref.H9739S

SECURITHERM dual control thermostatic shower mixer with:

- Anti-scalding safety: shuts off automatically if cold or hot water supply fails.
 - Scale-resistant thermostatic cartridge for temperature adjustment.
 - 1/4-turn ceramic head for flow rate adjustment.
 - Temperature control from 25 - 40°C with maximum temperature limiter set at 38°C.
 - Thermal shocks are possible without removing the control knob and shutting off the cold water.
 - Flow rate regulated at 9 lpm.
 - Chrome-plated brass body and CLASSIC controls.
 - M1/2" shower outlet.
 - F3/4" inlets with integrated filters and non-return valves.
 - Mixer with offset standard wall connectors, M1/2" M3/4".
- 10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic shower mixer - Ref.H9739S

| | |
|---------------------|---|
| Technology | SECURITHERM dual control thermostatic mixer |
| Flow rate | 9 lpm |
| Connector | M1/2" |
| Finish | Chrome-plated brass |
| Temperature limiter | 38 °C |

