

Recessed sequential thermostatic shower mixer

Ref. 790BOX-H9632

SECURITHERM mixer with no non-return valves in a waterproof housing



DESCRIPTION

Recessed sequential thermostatic shower mixer - [Ref.790BOX-H9632](#)

SECURITHERM individual sequential thermostatic shower mixer.

Opens/closes with cold water.

No risk of cross flow between the hot and cold water.

Mixer with non-return valves on the inlets (reduces bacterial development).

Anti-scalding failsafe: shuts off immediately if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

Temperature control: cold water up to 39°C with maximum temperature limiter set at 39°C.

Thermal shocks are possible.

Scale-resistant thermostatic sequential cartridge for adjusting flow rate and temperature.

Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.

Hygiene control lever L. 100mm.

M $\frac{3}{4}$ " inlets with integrated filters.

- Waterproof recessing housing behind a bright polished stainless steel cover plate 160 x 220mm.

- Adjustable recessing depth from 10 - 30mm.

- Order a wall-mounted outlet or shower head to complete.

10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Recessed sequential thermostatic shower mixer - [Ref.790BOX-H9632](#)

Technology	SECURITHERM thermostatic single control
Flow rate	9 lpm
Connector	M3/4"
Finish	Bright polished stainless steel
Temperature limiter	39 °C

