

# Recessed sequential thermostatic shower mixer

Ref. 790BOX-H9632

SECURITHERM mixer with no non-return valves in a  
waterproof housing



## DESCRIPTION

### Recessed sequential thermostatic shower mixer - [Ref.790BOX-H9632](#)

SECURITHERM individual sequential thermostatic shower mixer.  
Opens/closes with cold water.  
No risk of cross flow between the hot and cold water.  
Mixer with non-return valves on the inlets (reduces bacterial development).  
Anti-scalding failsafe: shuts off immediately if cold or hot water supply fails.  
Securitouch thermal insulation prevents burns.  
Temperature control: cold water up to 39°C with maximum temperature  
limiter set at 39°C.  
Thermal shocks are possible.  
Scale-resistant thermostatic sequential cartridge for adjusting flow rate and  
temperature.  
Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.  
Hygiene control lever L. 100mm.  
M<sup>3</sup>/4" inlets with integrated filters.  
• Waterproof recessing housing behind a bright polished stainless steel  
cover plate 160 x 220mm.  
• Adjustable recessing depth from 10 - 30mm.  
• Order a wall-mounted outlet or shower head to complete.  
10-year warranty.

## ADVANTAGES

## TECHNICAL CHARACTERISTICS

### Recessed sequential thermostatic shower mixer - [Ref.790BOX-H9632](#)

Technology	SECURITHERM thermostatic single control
Flow rate	9 lpm
Connector	M3/4"
Finish	Bright polished stainless steel
Temperature limiter	39 °C

