

Recessed sequential thermostatic shower mixer

Ref. H96BOX-H9631

SECURITHERM mixer in a waterproof housing with no non-return valves



DESCRIPTION

Recessed sequential thermostatic shower mixer - [Ref.H96BOX-H9631](#)

Recessed thermostatic shower mixer ideal for healthcare facilities, retirement homes, hospitals and clinics.

- Sequential mixer with no non-return valves on the inlets (reduces bacterial development).

No risk of cross flow between the hot and cold water.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

Sequential: opens/closes with cold water.

Scale-resistant thermostatic sequential cartridge for sequential adjustment flow rate and temperature.

Temperature control: cold water up to 39°C.

Maximum temperature limiter set at 39°C.

Thermal shocks are possible.

Flow rate regulated at 9 lpm (mixer only).

ERGO control knob.

Filters integrated in the M3/4" inlets.

Order a wall-mounted outlet or shower head to complete.

- Bright polished stainless steel cover plate 166 x 166mm.

- Waterproof recessing housing:

- Collar with waterproof seal.

- Hydraulic connection from the outside and maintenance from the front.

- Modular installation (rails, solid walls, panels).

- Compatible with wall finishes from 10 - 120mm (respecting the minimum recessing depth of 93mm).

- Suitable for standard or "pipe-in-pipe" supply.

- Stopcocks and flow rate adjustment, integrated filters and cartridge; all accessible from the front.

- Supplied in 2 kits: secure system purge without the sensitive elements.

- Suitable for people with reduced mobility.

- 10-year warranty.

Kit composition:

(H96BOX): recessing housing with protection, mixer valve configured for purging the system, connecting accessories.

(H9631): cover plate with control, mixer valve, waterproof collar, internal reinforcement.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Recessed sequential thermostatic shower mixer - [Ref.H96BOX-H9631](#)

Technology	SECURITHERM thermostatic sequential
Flow rate	Flow rate regulated at 9 lpm (mixer only)
Connector	1/2"
Finish	Chrome-plated brass
Temperature limiter	39 °C

