

Shower kit with thermostatic mixer

Ref. H9769SHYG

SECURITHERM Securitouch auto-draining thermostatic shower kit



DESCRIPTION

Shower kit with thermostatic mixer - Ref.H9769SHYG

SECURITHERM dual control thermostatic shower kit with auto-draining device includes:

- Mixer with scale-resistant thermostatic cartridge:
 - No non-return valves (less bacterial proliferation).
 - Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
 - Securitouch thermal insulation prevents burns.
 - Scale-resistant thermostatic cartridge for temperature adjustment.
 - ¼-turn ceramic head for flow rate adjustment.
 - Temperature control up to 41°C.
 - Double temperature limiter: 1st limiter set at 38°C, 2nd limiter set at 41°C.
 - Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
 - Flow rate limited to 9 lpm at 3 bar.
 - Ergonomic controls.
 - M½" shower outlet.
 - M¾" inlets with integrated filters.
 - Supplied with 2 offset standard wall connectors M½" M¾".
 - Chrome-plated shower head Ø 100mm with 5 jet options, with manual system for removing scale (ref. 813) and adjustable, wall-mounted, chrome-plated support (ref. 845).
 - Auto-draining device FM½" fits between the mixer outlet and the flexible hose, automatically drains the flexible and the shower head (ref. 880).
- 10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Shower kit with thermostatic mixer - Ref.H9769SHYG

Technology	SECURITHERM dual control thermostatic mixer, Securitouch, no-non-return valves
Length	260 mm
Flow rate	8 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	41 °C
Depth	84 mm

