

Thermostatic SECURITHERM securitouch auto-drain shower kit.

Ref. H9741KIT

Shower riser rail with thermostatic mixer

DESCRIPTION

Thermostatic SECURITHERM securitouch auto-drain shower kit. -

Ref.H9741KIT

SECURITHERM dual control thermostatic shower kit:

- Mixer with scale-resistant thermostatic cartridge:
- Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
- Securitouch thermal insulation prevents burns.
- Temperature control from 25 - 41°C.
- Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41°C.
- 1/4-turn ceramic head for flow rate adjustment.
- Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
- Flow rate regulated at 9 lpm.

ERGO control knobs.

M1/2" shower outlet.

F3/4" inlets with integrated filters and non-return valves.

- Supplied with 2 offset STOP/PURGE connectors, M1/2" M3/4", ideal for hospitals.

• Sliding shower head holder (ref. 813) on a chrome-plated riser rail (ref. 821) with soap dish and flexible shower hose (ref. 836T1).

• Shower hose retaining collar (ref. 830).

10-year warranty.

ADVANTAGES



TECHNICAL CHARACTERISTICS

Thermostatic SECURITHERM securitouch auto-drain shower kit. -

Ref.H9741KIT

Technology	SECURITHERM dual control thermostatic mixer, Securitouch
Length	286 mm
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	41 °C
Depth	95 mm

