

## SECURITHERM securitouch thermostatic shower kit

Ref. H9739KIT

Dual control thermostatic mixer



### DESCRIPTION

#### SECURITHERM securitouch thermostatic shower kit - Ref.H9739KIT

SECURITHERM dual control thermostatic shower kit:

- Mixer with scale-resistant, thermostatic cartridge:
  - Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
  - Temperature control from 25 - 40°C with temperature limiter set at 38°C.
  - 1/4-turn ceramic head for flow rate adjustment.
  - Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
  - Flow rate regulated at 9 lpm.

CLASSIC control knobs.

M1/2" shower outlet.

F3/4" inlets with integrated filters and non-return valves.

- Supplied with 2 STOP/CHECK wall connectors, M1/2" M3/4", ideal for hospitals.

• Sliding shower head holder (ref. 815) on a chrome-plated riser rail (ref. 836T1) with soap dish and flexible shower hose (ref. 836T1).

• Shower hose retaining collar (ref. 830).

10-year warranty.

### ADVANTAGES

### TECHNICAL CHARACTERISTICS

#### SECURITHERM securitouch thermostatic shower kit - Ref.H9739KIT

Technology	SECURITHERM dual control thermostatic mixer
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	38 °C
Width	281 mm

