

Shower kit with thermostatic mixer

Ref. H9739SKIT

Dual control thermostatic mixer



DESCRIPTION

Shower kit with thermostatic mixer - Ref.H9739SKIT

SECURITHERM dual control thermostatic shower kit:

- Mixer with scale-resistant, thermostatic cartridge:
 - Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
 - Temperature control from 25 - 40°C with temperature limiter set at 38°C.
 - 1/4-turn ceramic head for flow rate adjustment.
 - Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
 - Flow rate regulated at 9 lpm.

CLASSIC control knobs.

M1/2" shower outlet.

F3/4" inlets with integrated filters and non-return valves.

- Supplied with 2 offset standard wall connectors, M1/2" M3/4".
- Sliding shower head holder (ref. 815) on a chrome-plated riser rail (ref. 821) with soap dish and flexible shower hose (ref. 836T1).
- Shower hose retaining collar (ref. 830).

10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Shower kit with thermostatic mixer - Ref.H9739SKIT

Technology	SECURITHERM dual control thermostatic mixer
Length	281 mm
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Temperature limiter	38 °C
Depth	74 mm

