

Auto-draining shower kit with mechanical pressure-balancing (EP) mixer

Ref. 2739EPSHYG

Shower kit with pressure-balancing (EP) mixer



DESCRIPTION

Auto-draining shower kit with mechanical pressure-balancing (EP)

mixer - Ref.2739EPSHYG

Shower kit with single control mechanical mixer.

SECURITHERM shower kit with auto-draining device.

- Wall-mounted single control mixer with Securitouch thermal insulation to prevent burns.

Ø 40mm pressure-balancing (EP) ceramic cartridge with pre-set maximum temperature limiter.

Anti-scalding safety: HW flow is reduced if CW supply fails (and vice versa).

Constant temperature regardless of pressure or flow rate variations.

Body with smooth interior and low water volume (reduces niches where bacteria can develop).

Flow rate regulated at 9 lpm.

Chrome-plated brass body and sculptured control lever.

M1/2" shower outlet with integrated non-return valve.

Mixer with offset standard wall connectors, M1/2" M3/4", ideal for hospitals.

Filters and non-return valves.

- Chrome-plated shower head (ref. 813) with flexible shower hose (836T3) and chrome-plated, adjustable, wall-mounted support (ref. 845).

- Auto-draining device FM1/2" for installation between the flexible hose and the shower head, automatically drains the shower head and flexible hose (ref. 880).

Shower kit is ideal for healthcare facilities, retirement homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Auto-draining shower kit with mechanical pressure-balancing (EP)

mixer - [Ref.2739EPSHYG](#)

Technology	SECURITHERM EP, Securitouch
Length	182 mm
Flow rate	9 lpm
Connector	M1/2"
Finish	Chrome-plated brass
Depth	176 mm

