

## Auto-draining shower kit with EP mechanical mixer

Ref. 2539EPHYG

Shower kit with pressure-balancing mixer



### DESCRIPTION

#### Auto-draining shower kit with EP mechanical mixer - Ref.2539EPHYG

Shower kit with single control mechanical mixer.

SECURITHERM shower kit with auto-draining device:

- Mixer with Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Constant temperature regardless of pressure and flow rate variations.

Flow rate regulated at 9 lpm.

Chrome-plated brass body and sculptured control lever.

M $\frac{1}{2}$ " shower outlet with integrated non-return valve.

Mixer with 2 offset STOP/CHECK wall connectors M $\frac{1}{2}$ " M $\frac{3}{4}$ " ideal for hospitals.

Filters and non-return valves.

- Chrome-plated shower head (ref. 813) with flexible hose (ref. 834T3) and chrome-plated, wall-mounted tilting support (ref. 845).

- Anti-stagnation connector FM $\frac{1}{2}$ " for installation between lower outlet and flexible shower hose, for auto-draining of the flexible hose and shower head (ref. 880).

Shower kit ideal for healthcare facilities, nursing homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.

### ADVANTAGES

### TECHNICAL CHARACTERISTICS

#### Auto-draining shower kit with EP mechanical mixer - Ref.2539EPHYG

Technology	SECURITHERM EP
Flow rate	9 lpm
Connector	M $\frac{1}{2}$ "
Finish	Chrome-plated brass
Temperature limiter	39 °C
Width	175 mm

