

Auto-draining shower kit with EP mechanical mixer

Ref. 2239EPSHYG

Shower kit with pressure-balancing mixer



DESCRIPTION

Auto-draining shower kit with EP mechanical mixer - Ref.2239EPSHYG

Shower kit with single control mechanical mixer.

SECURITHERM shower kit with auto-draining device:

- Mixer with Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Flow rate regulated at 9 lpm.

Chrome-plated brass body and sculptured control lever.

M $\frac{1}{2}$ " shower outlet with integrated non-return valve.

Mixer with 2 offset standard wall connectors M $\frac{1}{2}$ " M $\frac{3}{4}$ ".

Filters and non-return valves.

- Chrome-plated shower head (ref. 811) with flexible hose (ref. 834T3) and chrome-plated, wall-mounted tilting support (ref. 845).

- Anti-stagnation connector FM $\frac{1}{2}$ " for installation between lower outlet and shower hose, automatically drains the flexible hose and shower head (ref. 880).

Ideal for healthcare facilities, nursing homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Auto-draining shower kit with EP mechanical mixer - Ref.2239EPSHYG

Technology	SECURITHERM EP
Flow rate	9 lpm
Connector	M $\frac{1}{2}$ "
Finish	Chrome-plated brass
Temperature limiter	39 °C
Width	175 mm

