

Recessed mechanical shower mixer

Ref. 254CBOX-2551

Recessed mechanical shower mixer in a waterproof housing



DESCRIPTION

Recessed mechanical shower mixer - Ref. 254CBOX-2551

Mechanical shower mixer which can be recessed. • Single control mixer with Ø 40mm ceramic cartridge. Pre-set maximum temperature limiter Thermal shocks are easy to undertake without removing the control lever or shutting off the cold water. Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head. Sculptured control lever. Order a wall-mounted outlet or shower head to complete. Waterproof recessing housing: - Collar with waterproof seal. - Hydraulic connection from the outside and maintenance from the front. - Adjusts to all types of installations (rails, solid walls, panels). - Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 93mm). - Suitable for standard or "pipe in pipe" supply. - Stopcocks and flow rate adjustment, filters, non-return valves and cartridge are all integrated and accessible from the front. - Supplied in 2 kits: secure system flush without sensitive elements. • Shower mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics. Suitable for people with reduced mobility. 10-year warranty. Kit composition: (254CBOX): recessing housing with protection, valve configured for system purge, connection accessories. (2551): control plate, valve, waterproof seal, interior reinforcement part.

ADVANTAGES



Thermal shock without removing the control lever



Ergonomic: solid lever is easy to grip



Recessed installation



Waterproof recessing housing

TECHNICAL CHARACTERISTICS

Recessed mechanical shower mixer - [Ref. 254CBOX-2551](#)

Flow rate	Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head
Finish	Chrome-plated brass
Supply	1/2"